

Kunststoffspritzguss

TYP	Min. EBH	Öffnungs- weg	Aufspann- platte	Holm-abstand	Zentrg. mm	Ausw.weg mm	Schnecke mm	Hub.vol. cm ³	Schließ- kraft	Ausführung
BA 750/315 CD	250mm	375 mm	H640 / V540	H404 / V304	125	160	40	201	75 t	
BA 500/200 CD	150mm	375 mm	H480 / V480	H304 / V304	125	160	30	84,8	50 t	
BA 500/200 CD	150mm	375 mm	H480 / V480	H304 / V304	125	160	30	84,8	50 t	
HM2F-HL 1000/210/60	185mm	475 mm	H760 / V760	H520 / V520	160	150	35	144,31	100 t	3 Aggregate. in 2K
VC 330/80	193mm	457 mm	H670 / V600	Holmlos	125	100	35	154	80 t	
ES 1350/250 HL	350mm	850 mm	H1050 / V900	Holmlos	160	200	60	735	250 t	
Allrounder 221-75-350	150mm	250 mm	H300 / V300	H220	110	50	22	30	35 t	
Allrounder 221-75-350	150mm	250 mm	H300 / V300	H220	110	50/pneum.	25	39	35 t	Vertikal
HM180/750	325mm	650 mm	H810 / V805	H570 / V520	160	150	45	358	180 t	

Wir bieten Qualität und Liefertreue in Serie!